



# DISH MACHINE COMPATIBILITY CHART

Updated as of 5/1/2012

## The Following Dish Machines Require SMART FABRICATION™ Modifications For Dishtable Compatibility.

<b>ADS (American Dish Machine)</b>	ADC44, ADC66	Sink bowl must be 20" from dish machine. Add <b>DTA-76</b> to soil dishtable.
	HT-25, SS-25	If dish machine is in corner, backsplash must be notched to 4" tall to clear handle. Add <b>DTA-78</b> to table that's on front of machine.
	AFC-3D, AF-3D, AF-ES, AFC-ES, AF-W, L60-3, L72-3, L90-3, 5-CD, 5-AG	<b>NO MODIFICATION NEEDED.</b>
<b>APEX</b>	TSC, TSC-Double	<b>NO MODIFICATION NEEDED.</b>
<b>Autochlor</b>	AC-44	No sinks or other obstructions within 20" of machine on soil side (add <b>DTA-76</b> ) or 10" of machine on clean side.
	A4, A5, D2	<b>NO MODIFICATION NEEDED.</b>
<b>Blakeslee</b>	D-8, D-9	If dish machine is in corner, right side backsplash must be notched to 4" tall to clear handle. Add <b>DTA-78</b> to the right table.
	R-L-40, RM50	Must maintain 13" clear on clean side of machine.
	R-CC-64, R-LL-80, R-MM-100	No sinks or other obstructions within 13" of machine on clean side.
<b>Burns</b>	A2	<b>NO MODIFICATION NEEDED.</b>
<b>Champion</b>	DH-5000 Genesis	If dish machine is in corner, right side backsplash must be notched to 3" tall to clear handle. Add <b>DTA-78</b> .
	40/44/54/64/66/70/72/76/80/84/86/90/94/100/106/110/120, D-HB, D-LF, D-FL, DH-1000, DH-2000	<b>NO MODIFICATION NEEDED.</b>
<b>CMA (Chemical Methods) Energymizer</b>	180	Right side sinks bowls must be 12" from dish machine. Add <b>DTA-76</b> if sink is on right table.
	44H, 44L, 66H, 66L	Sink bowl must be 12" from dish machine. Add <b>DTA-76</b> to soil dish table.
	B, AH, C, EST-AH, EST-C, CB	<b>NO MODIFICATION NEEDED.</b>
<b>Ecolab</b>	ES-4400, ES-6600, ES-8000	Left side sinks bowls must be 12" from dish machine.
	ES-4000	No modifications for straight thru operation. If used in a corner (ES-4000-CDR or CDL) one table backsplash must be notched to 4" tall. Add <b>DTA-78</b> to right (for CDR model) or left (for CDL model) table.
	ET-14	If sink is on right side of dish machine and deeper than 10", sink must be 16" from machine. Add <b>DTA-76</b> to soil table if required.
	ET-44	Right side sinks bowls must be 12" from dish machine. Add <b>DTA-76</b> if sink is on right table.
	WH-44, WH-66	Sink bowl or waste trough must be 14" from machine, regardless of direction flow. Add <b>DTA-76</b> to soil table.
	APEX TSC-V	This dish machine has a control box that can be relocated. In some situations, a 9" or deeper bowl on a right side dish table needs to be 18" from dish machine ( <b>DTA-76</b> ). This varies depending on the installation, and only the customer can determine if this is required.
	ES-2000, Inferno, Typhoon APEX HT	<b>NO MODIFICATION NEEDED.</b>
<b>Electrolux</b>	WT44	Sinks and troughs (and all other obstructions) recommended to be 20" from machine. Add <b>DTA-76</b> if required.
	WT65	If dish machine is in the corner, left side table backsplash and front rolled rim must both be cut down to 2" tall, add 2 <b>DTA-78</b> .
<b>Eurodib</b>	L21	<b>NO MODIFICATION NEEDED.</b>
	L25EK, L25EKDSP	Require a special machine opening 20 3/32 <b>DTA-77</b> . Front rolled edge needs 1" tall by 2" long flat section at machine, angled at end. Add <b>K-508A</b> . If a corner set up, left side table needs rear splash cut down to 1" tall for 2" closest to machine. Add <b>DTA-78</b> .
<b>Fagor</b>	FI-200W	Standard dish tables will NOT work with the dish machine due to depth of machine. Contact Advance Tabco for pricing.
	FI-120W	<b>NO MODIFICATION NEEDED.</b>
<b>Hobart</b>	AM-12	Right side sink bowls must be 12" from machine. Add <b>DTA-76</b> if sink is on right side. - <b>MACHINE DISCONTINUED.</b>
	AM-14	if sink is on right side of dish machine and is deeper than 10", sink must be 16" from dish machine. Add <b>DTA-76</b> to soil table if required. - <b>MACHINE IS DISCONTINUED.</b>
	AM-15	If dish machine is in corner, left side backsplash return must be notched to 4" tall to clear handle, add <b>DTA-78</b> . If soil table is on the left and dish machine is in corner, prerinse sink must move to 12" from dish machine. Add <b>DTA-76</b> .
	C-44/54/64/88, CL44/54, CLPS66/76, CRS-66/76/86/110	Sinks and troughs (and all other obstructions) recommended to be 20" from machine. Add <b>DTA-76</b> if required.
	SL-23/30,38DDU	A special dish machine opening is required. Add <b>DTA-72</b> to each dish table.
	CCS-66/76/86/110	Soil table opening similar to Hobart SL-23 sideloader (add <b>DTA-72</b> ), clean table opening 22". Sinks and troughs (and all other obstructions) recommended to be 20" from machine. Add <b>DTA-76</b> if required.

Continued on Page 2



# DISH MACHINE COMPATIBILITY CHART

Updated as of 5/1/2012

Continued From Page 1

## The Following Dish Machines Require SMART FABRICATION™ Modifications For Dishtable Compatibility.

	LT-1	NO MODIFICATION NEEDED.
<b>Insinger</b>	Admiral 44, 66, Speeder 64, 86 40-2	Must maintain 24" clear on both sides of machine. Add <b>DTA-76</b> to soil dishtable. A special dish machine opening (22") is required. Add <b>DTA-77</b> to each dishtable. Start with BSR series table. Add <b>K-508</b> to cut hole and install mounting flange. Add sink from page 78 if required. If additional length required use <b>DTA-56</b> .
	Commander 18-5, CS	<b>NO MODIFICATION NEEDED.</b>
<b>Intedge</b>	DW-50	<b>NO MODIFICATION NEEDED.</b>
<b>Jackson</b>	CREW Series	Clean (Exit) side sink bowl or waste trough must be 12" from machine. Add <b>DTA-76</b> to clean table if required.
	Tempstar HH	Machines built before January 2008, right side sinks bowls must be 12" from dish machine. Add <b>DTA-76</b> if sink is right table. (Not required for machines with control box on top of machine).
	Tempstar GPX	No changes. Verify where 27.5" wide booster heater will fit on floor under table.
	100, 150	Sink bowls on left side of machine must be 12" from dish machine. Add <b>DTA-76</b> to soil table if required. Left side tables must have 12" clear all the way to the floor (Including undershelves, legs, etc) - <b>MACHINES ARE DISCONTINUED.</b>
	TS-44, TSC-44, TS-66, TSC-66	Sink bowl or waste trough must be 14" from machine, regardless of direction flow. Add <b>DTA-76</b> to soil table.
	AJ Series, AJX Series	Left side sinks bowls must be 12" from dish machine. Right side must be 12" from machine. Add <b>DTA-76</b> to soil table if required.
	Jackson 10 (round)	Start with BSR series table. Add 2 <b>K-508</b> to cut hole and install mounting flange. Add sink from page 67 if required. If additional length required use <b>DTA-56</b> .
	200, Conserver, Tempstar	<b>NO MODIFICATION NEEDED.</b>
<b>Jet Tech</b>	747, F-22	Dish machine newer than 1/2001 no modification required. Older machines add <b>K-508</b> to each dishtable to notch front and rear back 1" and lower backsplash to 6" tall. F-22 dish machines made prior to 9/2002 right side sink bowl must be 14" from dish machine. Add <b>DTA-76</b> to soil table if required.
	F-22T	Right side sink bowls must be 14" from dish machine. Add <b>DTA-76</b> if sink is on right table. <b>- MACHINE IS DISCONTINUED.</b>
	X35C, X35D	<b>NO MODIFICATION NEEDED.</b>
<b>Knight</b>	KLE-235D, KLE-117C, KLE-117I, KLE-175GT	<b>NO MODIFICATION NEEDED.</b>
<b>Meiko</b>	DV80.2, DV120.2, DV200.2	If dish machine is in corner, backsplash and front rolled rim on left side table must be notched to 2" tall and 5" back to clear handle. Add <b>DTA-78</b> twice to left table.
	K-44, K-54, K-64, K-66, K-76 K-80, K-86, K-90, K-100	Sink bowl must be 12" from dish machine. Add <b>DTA-76</b> to soil dishtable.
<b>Moyer Diebel</b>	MH-60, MH-65	If dish machine is in corner, backsplash must be notched to 4" tall to clear handle. Add <b>DTA-78</b> to left table. Add a second <b>DTA-78</b> for left table to cut down front roll edge to 2". If dish machine is in corner and sink is on left dishtable, sink must be 16" from machine. Add <b>DTA-76</b> to left soil dishtable - <b>MACHINES ARE DISCONTINUED.</b>
	MD-2000	<b>NO MODIFICATION NEEDED.</b>
	MD-1000	<b>NO MODIFICATION NEEDED. - MACHINE IS DISCONTINUED.</b>
<b>Puritan</b>	PA-44	Left side sinks bowls must be 12" from dish machine. Right side must be 12" from machine. Add <b>DTA-76</b> to soil table if required.
	PA-1, PA-2, PA-HT	<b>NO MODIFICATION NEEDED.</b>
<b>Stero</b>	SDRA, SD-2RA	If dish machine is in corner, add 2 <b>DTA-56</b> and 1 <b>DTA-77</b> to left side table to provide manufacturer-recommended rear enclosure panel. If rear enclosure panel not desired, standard dish tables will fit with no modification. Right side sink bowls must be 12" from dish machine (26" if using SDRA-PKG). Add <b>DTA-76</b> if sink is on right table.
	SCT44, SCT66	Right side sinks bowls must be 12" from dish machine. Add <b>DTA-76</b> if sink is on right table.
	ER-44, ER-44-10, ER-66S, ER-76S, ER-76SC	Clean side turn down requires 1/2" x 3" notch (included in <b>DTA 77</b> price). No obstructions on clean side within 10" of machine. For ER-76SC only, no obstruction on soil side within 14" of machine ( <b>DTA-76</b> required).
	SC-20-1A, SC-25-1M, SC-25-3M	<b>NO MODIFICATION NEEDED.</b>
	<b>Vulcan-Hart</b>	3D20TF, 3D2FCD